

**Description**

Thread Size: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL41812
Minimum Qty (MOQ):	5
NSN:	5320-01-269-0872
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL41-8-12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.0947 Inches Minimum And 0.0967 Inches Maximum
<b>Shank Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Style:</b>	Pin-rievet, Straight, Threaded
<b>Head Major Diameter:</b>	0.3948 Inches Maximum
<b>Grip Length:</b>	0.439 Inches Minimum And 0.500 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL41-8-12](https://military-fasteners.com/pins/pin_rivets/HL41-8-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.