

Description

Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL41812
Minimum Qty (MOQ):	5
NSN:	5320-01-269-0872
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL41-8-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Head Style:	Flush Countersunk
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rievet, Straight, Threaded
Head Major Diameter:	0.3948 Inches Maximum
Grip Length:	0.439 Inches Minimum And 0.500 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL41-8-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.