

Description

HL410VAZ-6-6 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL410VAZ66
Minimum Qty (MOQ):	5
NSN:	5320-01-462-0424
Schedule B:	8108.90.8000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL410VAZ6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.700 Inches Nominal
Head Style:	Err-090
Head Height:	0.050 Inches Nominal
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.2172 Inches Minimum And 0.2182 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.305 Inches Nominal
Lubrication:	Cetyl Alcohol
Grip Length:	0.3750 Inches Nominal
Nominal Thread Size:	0.190 Inches
Special Features:	0.031 In Oversize Shank Dia; Color Coded Black
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Alloy Overall
Surface Treatment Document And Classification:	Hi-kote 1, Spec 294, Cagc 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL410VAZ6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.