

Description

Fastener Length: 15/16", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL48107
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-066-9440
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL48-10-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.928 Inches Minimum And 0.948 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.098 Inches Minimum And 0.112 Inches Maximum
<b>Width Between Flats:</b>	0.1270 Inches Minimum And 0.1295 Inches Maximum
<b>Shank Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.472 Inches Minimum And 0.502 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.443 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	258,fscm 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL48-10-7](https://military-fasteners.com/rivets/pin_rivets/HL48-10-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.