

Description

Fastener Length: 3/4", Thread Size: 5/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL4857
Minimum Qty (MOQ):	10
NSN:	5320-01-259-2473
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL48-5-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.740 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.060 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.080 Inches Maximum
<b>Shank Diameter:</b>	0.1630 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.443 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL48-5-7](https://military-fasteners.com/pins/pin_rivets/HL48-5-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.