

P/N HL48-6-3

Military-Fasteners.com

#### Description

Fastener Length: 33/64", Thread Size: 3/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	HL4863
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-658-3842
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



# P/N HL48-6-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.503 Inches Minimum And 0.523 Inches Maximum
Head Style:	Err-090
Head Height:	0.064 Inches Minimum And 0.074 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.357 Inches Minimum And 0.377 Inches Maximum
End Item Identification:	W/s: Ticonderoga Class Cg (47); Missile, All-weather Anti-ship, Harpoon (agm-84); Aircraft, Awacs, E-3a; Engine, Aircraft, Tf-33-p-7 (c- 141a/b); Aircraft, Eagle F-15; Aircraft, Hx Unique; Aircraft, Hornet F/a-18; Aircraft, Harrier Av-8b
Grip Length:	0.193 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/pin\_rivets/HL48-6-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.