

**Description**

Fastener Length: 41/64", Thread Size: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4865
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-291-5404
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N HL48-6-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.627 Inches Minimum And 0.647 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.064 Inches Minimum And 0.074 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.357 Inches Minimum And 0.377 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.317 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	258,fscm 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL48-6-5](https://military-fasteners.com/rivets/pin_rivets/HL48-6-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.