

**Description**

HL48-6-6 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | HL4866                      |
| Minimum Qty (MOQ):      | 5                           |
| NSN:                    | 5320-01-012-7428            |
| Schedule B:             | 7318.23.0000                |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL48-6-6 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 0.690 Inches Minimum And 0.710 Inches Maximum  |
| <b>Head Style:</b>                                    | Err-090  |
| <b>Head Height:</b>                                   | 0.064 Inches Minimum And 0.074 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.0791 Inches Minimum And 0.0806 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.1890 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.357 Inches Minimum And 0.377 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol  |
| <b>End Item Identification:</b>                       | W/s:engine, Aircraft F-117, Pw-100 (c-17a); Aircraft, Hornet F/a-18; Aircraft, Eagle F-15; Joint Stars Target Radar System; Fms-aircraft, Hornet F/a-18; Aircraft, Airlifter C-17a; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130) |
| <b>Grip Length:</b>                                   | 0.380 Inches Maximum   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches   |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | 258,fscm 73197 Mfr Ref Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL48-6-6](https://military-fasteners.com/pins/pin_rivets/HL48-6-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.