

P/N HL48-6-6

Military-Fasteners.com

Description

HL48-6-6 Pin-Rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	HL4866
Minimum Qty (MOQ):	5
NSN:	5320-01-012-7428
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N HL48-6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Err-090
Head Height:	0.064 Inches Minimum And 0.074 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.357 Inches Minimum And 0.377 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	W/s:engine, Aircraft F-117, Pw-100 (c-17a); Aircraft, Hornet F/a-18; Aircraft, Eagle F-15; Joint Stars Target Radar System; Fms-aircraft, Hornet F/a-18; Aircraft, Airlifter C-17a; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130)
Grip Length:	0.380 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/pins/pin_rivets/HL48-6-6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.