

Description

Fastener Length: 49/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4867
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-094-7412
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL48-6-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.752 Inches Minimum And 0.772 Inches Maximum
Head Style:	Err-090
Head Height:	0.064 Inches Minimum And 0.074 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.357 Inches Minimum And 0.377 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.432 Inches Minimum And 0.442 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL48-6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.