

Description

Fastener Length: 33/64", Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | HL4882 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-191-2151 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N HL48-8-2 Specifications

| | |
|-------------------------------------------------------|----------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.510 Inches Minimum And 0.530 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.077 Inches Minimum And 0.090 Inches Maximum |
| Width Between Flats: | 0.0947 Inches Minimum And 0.0967 Inches Maximum |
| Shank Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Head Major Diameter: | 0.415 Inches Minimum And 0.440 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.130 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.250 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | 258,fscm 73197 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL48-8-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.