

Description

Fastener Length: 31/32", Thread Size: 11/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL50510
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-388-9078
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL50-5-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Bronze
Fastener Length:	0.957 Inches Minimum And 0.977 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Tip Diameter:	0.157 Inches Minimum And 0.159 Inches Maximum
Grip Length:	0.620 Inches Minimum And 0.630 Inches Maximum
Minimum Tensile Strength:	194000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Shear Strength:	4010 Double Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL50-5-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.