

Description

protruding shear head - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | HL5064 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-794-8274 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N HL50-6-4 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.595 Inches Minimum And 0.615 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Grip Length: | 0.255 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL50-6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.