

## P/N HL50-8-17

## **Description**

straight, threaded

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL50817

Minimum Qty (MOQ): 5

NSN: 5320-00-498-9885

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









<sup>\*</sup> See page 2 for technical characteristics

# P/N HL50-8-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.477 Inches Minimum And 1.497 Inches Maximum
Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.095 Inches Minimum And 0.097 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Grip Length:	1.067 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Shear Strength:	5000 Single Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/HL50-8-17">https://military-fasteners.com/pins/pin\_rivets/HL50-8-17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="here">here</a> to complete your order.