

Description

100°, flush shear head - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL5156
Minimum Qty (MOQ):	10
NSN:	5320-01-388-9079
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL51-5-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Bronze
Fastener Length:	0.707 Inches Minimum And 0.727 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0801 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Head Major Diameter:	0.2564 Inches Minimum And 0.2612 Inches Maximum
End Item Identification:	W/s: Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130)
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 8640 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL51-5-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.