

**Description**

Diameter: 13/64", Grip Length: 1/8", protruding shear head, oversized for HL18, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | HL62PB62                                    |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5320-01-293-6679                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N HL62PB6-2 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Fastener Length:</b>                               | 0.440 Inches Minimum And 0.460 Inches Maximum   |
| <b>Head Style:</b>                                    | Err-090   |
| <b>Head Height:</b>                                   | 0.045 Inches Minimum And 0.055 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.0791 Inches Minimum And 0.0806 Inches Maximum   |
| <b>Shank Diameter:</b>                                | 0.2016 Inches Minimum And 0.2026 Inches Maximum   |
| <b>Shank Style:</b>                                   | Pin-riquet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.295 Inches Minimum And 0.315 Inches Maximum   |
| <b>Lubrication:</b>                                   | Cetyl Alcohol   |
| <b>Grip Length:</b>                                   | 0.130 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches  |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch   |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this pin-riquet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_riquets/HL62PB6-2](https://military-fasteners.com/pins/pin_riquets/HL62PB6-2) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.