

P/N HL62PB6-3

Description

Diameter: 13/64", Grip Length: 3/16", protruding shear head, oversized for hl18, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: HL62PB63

Minimum Qty (MOQ): 20

NSN: 5320-01-043-0071

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









P/N HL62PB6-3 Specifications

Right-hand Fastener Length: 0.503 Inches Minimum And 0.523 Inches Maximum Head Style: Err-090 Head Height: 0.045 Inches Minimum And 0.055 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.02026 Inches Maximum Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall		
Asstener Length: 0.503 Inches Minimum And 0.523 Inches Maximum Head Style: Err-090 Head Height: 0.045 Inches Minimum And 0.0856 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Oq-p-416.ty 2.cl 2 Fed Spec Single Treatment Response Overall Oq-p-416.ty 2.cl 2 Fed Spec Single Treatment Response Overall	Thread Class:	3a
Head Style: Head Height: O.045 Inches Minimum And O.055 Inches Maximum Width Between Flats: O.0791 Inches Minimum And O.0806 Inches Maximum Shank Diameter: O.2016 Inches Minimum And O.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: O.295 Inches Minimum And O.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: O.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: Nominal Thread Size: O.190 Inches Shear Strength: Steel Comp Ed340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall Oq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Orsell Treatment: Cadmium Overall Oq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Thread Direction:	Right-hand
Head Height: 0.045 Inches Minimum And 0.055 Inches Maximum Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Fastener Length:	0.503 Inches Minimum And 0.523 Inches Maximum
Width Between Flats: 0.0791 Inches Minimum And 0.0806 Inches Maximum 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Material: Material Document And Classification: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Gup-416.ty 2,cl 2 Fed Spec Single Treatment Response Overall Ocentified Assimination 0.2016 Inches Maximum 0.2026 Inches Maximum 0.2056 Inches Maximum 0.2095 Inches Maximum	Head Style:	Err-090
Shank Diameter: 0.2016 Inches Minimum And 0.2026 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.295 Inches Minimum And 0.315 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Head Major Diameter: Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum 160000 Pounds Per Square Inch Nominal Thread Size: Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Cadmium Overall Surface Treatment Document And Classification: Classification: Cetyl Alcohol 0.193 Inches Maximum 0.193 Inches Maximum 0.193 Inches Maximum 0.194 Inches 0.190 Inches 0.19	Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Shank Style:	Pin-rivet, Straight, Threaded
Grip Length: O.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: O.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Gurface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 5hear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Lubrication:	Cetyl Alcohol
Minimum Tensile Strength: Nominal Thread Size: Shear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Grip Length:	0.193 Inches Maximum
Nominal Thread Size: 5hear Strength: 95000 Single Pounds Per Square Inch Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Surface Treatment Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	32
Shear Strength: 95000 Single Pounds Per Square Inch Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Classification:	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Nominal Thread Size:	0.190 Inches
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Classification:	Shear Strength:	95000 Single Pounds Per Square Inch
Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall	Material Document And	
Surface Treatment Document And Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall		
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall		Cadinian Overan
Thread Series Designator: Unjf	Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unjf

How to Order

Order this pin- rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL62PB6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL62PB6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL62PB6-3 and selecting the quantity you want then click "add to cart".