

P/N HL62PB8-15

Military-Fasteners.com

Description

protruding shear head - oversized for hl18 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	HL62PB815
Minimum Qty (MOQ):	5
NSN:	5320-01-113-2305
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL62PB8-15 Specifications

Thread Class:3aThread Direction:Right-handFastener Length:1.323 Inches Minimum And 1.343 Inches MaximumHead Style:Err-090Head Height:0.059 Inches Minimum And 0.069 Inches MaximumWidth Between Flats:0.0947 Inches Minimum And 0.0967 Inches MaximumShank Diameter:0.2641 Inches Minimum And 0.2651 Inches MaximumShank Style:Pin-rivet, Straight, ThreadedHead Major Diameter:0.387 Inches Minimum And 0.412 Inches MaximumLubrication:Cetyl Alcohol, Spec 305, Hi-shear Corp
Fastener Length:1.323 Inches Minimum And 1.343 Inches MaximumHead Style:Err-090Head Height:0.059 Inches Minimum And 0.069 Inches MaximumWidth Between Flats:0.0947 Inches Minimum And 0.0967 Inches MaximumShank Diameter:0.2641 Inches Minimum And 0.2651 Inches MaximumShank Style:Pin-rivet, Straight, ThreadedHead Major Diameter:0.387 Inches Minimum And 0.412 Inches Maximum
Head Style:Err-090Head Height:0.059 Inches Minimum And 0.069 Inches MaximumWidth Between Flats:0.0947 Inches Minimum And 0.0967 Inches MaximumShank Diameter:0.2641 Inches Minimum And 0.2651 Inches MaximumShank Style:Pin-rivet, Straight, ThreadedBead Major Diameter:0.387 Inches Minimum And 0.412 Inches Maximum
Head Height:0.059 Inches Minimum And 0.069 Inches MaximumWidth Between Flats:0.0947 Inches Minimum And 0.0967 Inches MaximumShank Diameter:0.2641 Inches Minimum And 0.2651 Inches MaximumShank Style:Pin-rivet, Straight, ThreadedHead Major Diameter:0.387 Inches Minimum And 0.412 Inches Maximum
Width Between Flats:0.0947 Inches Minimum And 0.0967 Inches MaximumShank Diameter:0.2641 Inches Minimum And 0.2651 Inches MaximumShank Style:Pin-rivet, Straight, ThreadedHead Major Diameter:0.387 Inches Minimum And 0.412 Inches Maximum
Shank Diameter: 0.2641 Inches Minimum And 0.2651 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.387 Inches Minimum And 0.412 Inches Maximum
Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.387 Inches Minimum And 0.412 Inches Maximum
Head Major Diameter: 0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication: Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification: Aircraft, Stratofortress B-52; joint Stars Target Radar System; aircraft, Stratolifter C-135
Grip Length: 0.933 Inches Minimum And 0.943 Inches Maximum
Thread Quantity Per Inch: 28
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Nominal Thread Size: 0.250 Inches
Shear Strength: 95000 Single Pounds Per Square Inch
Material: Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 1st Material Response Overa
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification: Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf

How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/pin_rivets/HL62PB8-15</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.