

Description

Fastener Length: 1-1/8", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL63PB1010
Minimum Qty (MOQ):	10
NSN:	5320-00-968-9209
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL63PB10-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3266 Inches Minimum And 0.3276 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.4689 Inches Minimum And 0.4739 Inches Maximum
End Item Identification:	Wsd: Aircraft, Hercules C-130; Aircraft, Stratolifter C-135; Aircraft, Sof (ac-130h, Mc-130h, Ec-130e, Hc-130)
Grip Length:	0.630 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Steel Comp 8740 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,c1 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB10-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.