

Description

100°, flush shear head - oversized for hl19 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL63PB107
Minimum Qty (MOQ):	5
NSN:	5320-01-499-8107
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N HL63PB10-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.9275 Inches Minimum And 0.9475 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.6699 Inches Minimum And 0.6709 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.4689 Inches Minimum And 0.4739 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification:	A-10 Thunderbolt
Grip Length:	0.4325 Inches Minimum And 0.4425 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.3125 Inches
Shear Strength:	67200 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Assn Std 1st Material Response Overall Or Mil-s-5626 Assn Std 2nd Material Response Overall Or Mil-s-6049 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB10-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.