



Military-Fasteners.com

P/N HL63PB10-8

Description

100°, flush shear head - oversized for hl19 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HL63PB108 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-436-0106 |



* See page 2 for technical characteristics

P/N HL63PB10-8 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.000 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.1270 Inches Minimum And 0.1295 Inches Maximum |
| Shank Diameter: | 0.3266 Inches Minimum And 0.3276 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.4689 Inches Minimum And 0.4739 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.500 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB10-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.