

Description

100°, flush shear head - oversized for hl19 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL63PB612
Minimum Qty (MOQ):	10
NSN:	5320-01-498-1567
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL63PB6-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.075 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.1875 Inches Nominal
Shank Style:	Err-090
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Grip Length:	0.325 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Tip Radius: 0.03125 In. Nominal
Material:	Steel Comp 4340 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type2,class2and Cetyl Alcohol Lube/hs Spec 305 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB6-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.