

Description

Fastener Length: 1-53/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL63PB624
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-254-7326
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL63PB6-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.815 Inches Minimum And 1.835 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.791 Inches Minimum And 0.806 Inches Maximum
Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Head Major Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	1.505 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL63PB6-24 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.