

**Description**

flush shear head, oversized for hl19, alloy steel, cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL63PB68
Minimum Qty (MOQ):	20
NSN:	5320-01-177-9794
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N HL63PB6-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.815 Inches Minimum And 0.835 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.0791 Inches Minimum And 0.0806 Inches Maximum
<b>Shank Diameter:</b>	0.2016 Inches Minimum And 0.2026 Inches Maximum
<b>Head Major Diameter:</b>	0.3016 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.505 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type Ii Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL63PB6-8](https://military-fasteners.com/pins/pin_rivets/HL63PB6-8) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.