

Description

Fastener Length: 1-17/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL63PB814
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-498-1561
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL63PB8-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.270 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.250 Inches Nominal
Shank Style:	Err-090
Head Major Diameter:	0.3898 Inches Minimum And 0.3948 Inches Maximum
Grip Length:	0.395 Inches Nominal
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Tip Radius: 0.03125 In. Nominal
Material:	Steel Comp 4340 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type2,class2and Cetyl Alcohol Lube/hs Spec 305 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB8-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.