

Description

flush shear head, oversized for hl19, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL63PB815
Minimum Qty (MOQ):	5
NSN:	5320-01-261-4348
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL63PB8-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.333 Inches Nominal
Head Style:	Cooper's
Head Height:	0.061 Inches Minimum And 0.066 Inches Maximum
Width Between Flats:	0.128 Inches Nominal
Shank Diameter:	0.327 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.389 Inches Minimum And 0.394 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.938 Inches Maximum
Nominal Thread Size:	0.312 Inches
Shear Strength:	16000 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL63PB8-15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.