

**Description**

flush shear head, oversized for hl19, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL63PB815
Minimum Qty (MOQ):	5
NSN:	5320-01-261-4348
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL63PB8-15 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.333 Inches Nominal
<b>Head Style:</b>	Cooper's
<b>Head Height:</b>	0.061 Inches Minimum And 0.066 Inches Maximum
<b>Width Between Flats:</b>	0.128 Inches Nominal
<b>Shank Diameter:</b>	0.327 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.389 Inches Minimum And 0.394 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.938 Inches Maximum
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Shear Strength:</b>	16000 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL63PB8-15](https://military-fasteners.com/pins/pin_rivets/HL63PB8-15) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.