

Description

Fastener Length: 1/4", Thread Size: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL63PB817
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-471-1264
Schedule B:	7318.24.0000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N HL63PB8-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.253 Inches Minimum And 0.254 Inches Maximum
Head Style:	Countersunk W/reverse Chamfer
Head Height:	0.052 Inches Nominal
Width Between Flats:	0.130 Inches Nominal
Shank Diameter:	0.241 Inches Nominal
Shank Style:	Pin-riquet, Straight, Threaded
Head Major Diameter:	0.388 Inches Nominal
Grip Length:	1.062 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.241 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB8-17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.