

P/N HL63PB8-17

Description

Fastener Length: 1/4", Thread Size: 15/64"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: HL63PB817

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-471-1264

Schedule B: 7318.24.0000

ECCN: 9A991



^{*} See page 2 for technical characteristics

P/N HL63PB8-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.253 Inches Minimum And 0.254 Inches Maximum
Head Style:	Countersunk W/reverse Chamfer
Head Height:	0.052 Inches Nominal
Width Between Flats:	0.130 Inches Nominal
Shank Diameter:	0.241 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.388 Inches Nominal
Grip Length:	1.062 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.241 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL63PB8-17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/pin_rivets/HL63PB8-17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/pin_rivets/HL63PB8-17 and selecting the quantity you want then click "add to cart".