

Description

protruding tension head oversized for use with HL20, alloy steel cadmium plated, HL64 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL64PB106
Minimum Qty (MOQ):	5
NSN:	5320-01-549-8922
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL64PB10-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Blue, Violet
Head Style:	Cooper's
Head Height:	2.6 Millimeters Maximum
Shank Diameter:	0.328 Inches Nominal
Shank Style:	Stump
Head Major Diameter:	9.9 Millimeters Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.375 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	9200 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Shear Strength:	16000 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL64PB10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.