

Description

protruding tension head oversized for use with HL20, alloy steel cadmium plated, HL64 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HL64PB106 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-549-8922 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N HL64PB10-6 Specifications

| | |
|-----------------------------------|-------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Identification Code Color: | Blue, Violet |
| Head Style: | Cooper's |
| Head Height: | 2.6 Millimeters Maximum |
| Shank Diameter: | 0.328 Inches Nominal |
| Shank Style: | Stump |
| Head Major Diameter: | 9.9 Millimeters Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.375 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 9200 Pounds Per Square Inch |
| Nominal Thread Size: | 0.312 Inches |
| Shear Strength: | 16000 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL64PB10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.