

**Description**

protruding tension head oversized for use with HL20, alloy steel cadmium plated, HL64 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL64PB106
Minimum Qty (MOQ):	5
NSN:	5320-01-549-8922
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N HL64PB10-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Identification Code Color:</b>	Blue, Violet
<b>Head Style:</b>	Cooper's
<b>Head Height:</b>	2.6 Millimeters Maximum
<b>Shank Diameter:</b>	0.328 Inches Nominal
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	9.9 Millimeters Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.375 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	9200 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Shear Strength:</b>	16000 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL64PB10-6](https://military-fasteners.com/rivets/pin_rivets/HL64PB10-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.