

Description

protruding tension head oversized for hl20 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL64PB614
Minimum Qty (MOQ):	5
NSN:	5320-01-456-1453
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL64PB6-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.200 Inches Maximum
Head Style:	Err-090
Head Height:	0.074 Inches Nominal
Width Between Flats:	0.080 Inches Nominal
Shank Diameter:	0.202 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.367 Inches Nominal
Lubrication:	Cetyl Alcohol
Grip Length:	0.875 Inches Nominal
Minimum Tensile Strength:	3180 Pounds Per Square Inch
Nominal Thread Size:	10.000 Inches
Shear Strength:	6130 Double Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL64PB6-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.