

# P/N HL64PB6-14

## **Description**

protruding tension head oversized for hI20 - alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL64PB614

Minimum Qty (MOQ):

NSN: 5320-01-456-1453

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N HL64PB6-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.200 Inches Maximum
Head Style:	Err-090
Head Height:	0.074 Inches Nominal
Width Between Flats:	0.080 Inches Nominal
Shank Diameter:	0.202 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.367 Inches Nominal
Lubrication:	Cetyl Alcohol
Grip Length:	0.875 Inches Nominal
Minimum Tensile Strength:	3180 Pounds Per Square Inch
Nominal Thread Size:	10.000 Inches
Shear Strength:	6130 Double Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/HL64PB6-14">https://military-fasteners.com/pins/pin\_rivets/HL64PB6-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.