

Description

Diameter: 13/64", Grip Length: 7/16", protruding tension head, oversized for hl20, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL64PB67
Minimum Qty (MOQ):	10
NSN:	5320-00-835-2195
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N HL64PB6-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.753 Inches Minimum And 0.773 Inches Maximum
Head Height:	0.064 Inches Minimum And 0.074 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.202 Inches Minimum And 0.203 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.758 Inches Minimum And 0.778 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	W/s:helicopter, Hh-53h Pave Low; Aircraft, Starlifter C-141; Helicopter, Iroquois Hh/uh-1; Helicopter, Iroquois Uh-1; Aircraft, Thunderbolt II, A-10; Helicopter, Mh-53e; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, Stratolifter C-135; Joint Stars Target Radar System; Helicopter, Green Giant H-3
Grip Length:	0.443 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL64PB6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.