

Description

Diameter: 13/64", Grip Length: 7/16", protruding tension head, oversized for hl20, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | HL64PB67                    |
| Minimum Qty (MOQ):      | 10                          |
| NSN:                    | 5320-00-835-2195            |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



\* See page 2 for technical characteristics

## P/N HL64PB6-7 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 0.753 Inches Minimum And 0.773 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.064 Inches Minimum And 0.074 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.079 Inches Minimum And 0.081 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.202 Inches Minimum And 0.203 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.758 Inches Minimum And 0.778 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol  |
| <b>End Item Identification:</b>                       | W/s:helicopter, Hh-53h Pave Low; Aircraft, Starlifter C-141; Helicopter, Iroquois Hh/uh-1; Helicopter, Iroquois Uh-1; Aircraft, Thunderbolt II, A-10; Helicopter, Mh-53e; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, Stratolifter C-135; Joint Stars Target Radar System; Helicopter, Green Giant H-3 |
| <b>Grip Length:</b>                                   | 0.443 Inches Maximum   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches   |
| <b>Material:</b>                                      | Steel Comp 4130 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-6758 Mil Spec Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL64PB6-7](https://military-fasteners.com/pins/pin_rivets/HL64PB6-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.