

**Description**

protruding tension head oversized for hl20, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                       |
|-------------------------|-----------------------|
| SKU / Model:            | HL64PB815             |
| Minimum Qty (MOQ):      | 5                     |
| NSN:                    | 5320-00-119-4973      |
| ECCN:                   | EAR99                 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE  
AVAILABLE

## P/N HL64PB8-15 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 1.323 Inches Minimum And 1.343 Inches Maximum  |
| <b>Head Style:</b>                                    | Err-090  |
| <b>Head Height:</b>                                   | 0.077 Inches Minimum And 0.090 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.095 Inches Minimum And 0.097 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.264 Inches Minimum And 0.265 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rievet, Straight, Threaded   |
| <b>Head Major Diameter:</b>                           | 0.415 Inches Minimum And 0.440 Inches Maximum  |
| <b>End Item Identification:</b>                       | W/s: Aircraft, Thungerbolt li, A-10; Aircraft, Stratolifter C-135; Helicopter, Super Jolly H-53; Aircraft, Awacs, E-3a; Helicopter, Hx Unique; Aircraft, Stratofortress B-52 |
| <b>Grip Length:</b>                                   | 0.943 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Nominal Thread Size:</b>                           | 0.250 Inches   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rievets/HL64PB8-15](https://military-fasteners.com/pins/pin_rievets/HL64PB8-15) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.