

P/N HL64PB8-15

Military-Fasteners.com

Description

protruding tension head oversized for hl20, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	HL64PB815
Minimum Qty (MOQ):	5
NSN:	5320-00-119-4973
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



P/N HL64PB8-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.323 Inches Minimum And 1.343 Inches Maximum
Head Style:	Err-090
Head Height:	0.077 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.095 Inches Minimum And 0.097 Inches Maximum
Shank Diameter:	0.264 Inches Minimum And 0.265 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.415 Inches Minimum And 0.440 Inches Maximum
End Item Identification:	W/s: Aircraft, Thungerbolt Ii, A-10; Aircraft, Stratolifter C-135; Helicopter, Super Jolly H-53; Aircraft, Awacs, E-3a; Helicopter, Hx Unique; Aircraft, Stratofortress B-52
Grip Length:	0.943 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/pins/pin_rivets/HL64PB8-15</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.