

## **P/N HL64PB8-2**

### **Description**

Fastener Length: 33/64", Thread Size: 1/4", HL64 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	HL64PB82
Minimum Qty (MOQ):	5
NSN:	5320-01-412-7955
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# **P/N HL64PB8-2 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.510 Inches Minimum And 0.530 Inches Maximum
Head Style:	Err-090
Head Height:	0.077 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2641 Inches Minimum And 0.2651 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.415 Inches Minimum And 0.440 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.120 Inches Minimum And 0.130 Inches Maximum
Minimum Tensile Strength:	5820 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Shear Strength:	10490 Double Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl64 Manufacturers Standard

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2">https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2">https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2">https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2">https://military-fasteners.com/rivets/pin\_rivets/HL64PB8-2</a> and selecting the quantity you want then click "add to cart".