

Description

100°, flush ms24694 tension head - oversized for hl21 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL65PB610
Minimum Qty (MOQ):	10
NSN:	5320-01-039-3958
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N HL65PB6-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.940 Inches Minimum And 0.960 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3813 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.630 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	6130 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL65PB6-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.