

Description

Flush ms24694 tension head, oversized for hl21, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL65PB614
Minimum Qty (MOQ):	5
NSN:	5320-01-425-1408
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL65PB6-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.190 Inches Minimum And 1.210 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3765 Inches Minimum And 0.3813 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.870 Inches Minimum And 0.880 Inches Maximum
Minimum Tensile Strength:	3180 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	6130 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	1/64" Oversized.
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl65 Manufacturers Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL65PB6-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.