

Description

100°, flush ms24694 tension head - oversized for hl21 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL65PB62
Minimum Qty (MOQ):	10
NSN:	5320-01-458-1461



* See page 2 for technical characteristics

P/N HL65PB6-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.450 Inches Nominal
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.2016 Inches Minimum And 0.2026 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3765 Inches Minimum And 0.3813 Inches Maximum
Grip Length:	0.125 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 431 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL65PB6-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.