

Description

Fastener Length: 2-13/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL65PB829
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-359-6985
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HL65PB8-29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	2.1975 Inches Minimum And 2.2175 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2641 Inches Minimum And 0.2651 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.5018 Inches Minimum And 0.5066 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	1.8075 Inches Minimum And 1.8175 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.2500 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL65PB8-29 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.