

**Description**

shear application, aluminum alloy, red anodized, aluminum alloy, HL70 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL70TW5
Minimum Qty (MOQ):	10
NSN:	5320-00-064-0154
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N HL70TW5 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Identification Code Color:</b>	Gray
<b>Collar Outside Diameter:</b>	0.288 Inches Minimum And 0.292 Inches Maximum
<b>Collar Overall Height:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.166 Inches Minimum And 0.173 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Special Features:</b>	Color Gray Or Color Blue
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Collar
<b>Material:</b>	Aluminum Alloy 5052 Washer Or Aluminum Alloy 2024 Washer
<b>Material:</b>	Aluminum Alloy 2024 Body
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rievet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rievet+collars/HL70TW5](https://military-fasteners.com/collars/pin_rievet+collars/HL70TW5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.