

Description

collar and washer assembly. shear application, aluminum alloy, red color, anodized, washer aluminum alloy, HL70 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL70TW6
Minimum Qty (MOQ):	10
NSN:	5320-00-064-0152
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL70TW6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Gray
Collar Outside Diameter:	0.303 Inches Minimum And 0.307 Inches Maximum
Collar Overall Height:	0.437 Inches Minimum And 0.457 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.192 Inches Minimum And 0.200 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Color Gray Or Color Blue
Heat Treatment:	T-6 Solution Heat Treated Collar
Material:	Aluminum Alloy 5052 Washer Or Aluminum Alloy 2024 Washer
Material:	Aluminum Alloy 2024 Body
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL70TW6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.