

Description

Thread Size: 3/8", HL75 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL7512AW |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5320-00-023-4439 |
| Schedule B: | 7318.22.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N HL75-12AW Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.675 Inches Minimum And 0.685 Inches Maximum |
| Collar Overall Height: | 0.667 Inches Nominal |
| Collar Inside Diameter: | 0.490 Inches Nominal |
| End Item Identification: | 1520-01-106-9519 |
| Nominal Thread Size: | 0.375 Inches |
| Collar Style: | Threaded (break Off) Type |
| Special Features: | Cres Washer Included |
| Material: | Steel Comp 303se Overall |
| Material Document And Classification: | Qq-s-764 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL75-12AW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.