

Description

Self-aligning, 303 stainless steel, tension application, cadmium plated, hi-lok, HL75 Series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL755A |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-123-0929 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N HL75-5A Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.355 Inches Minimum And 0.365 Inches Maximum |
| Collar Overall Height: | 0.427 Inches Minimum And 0.457 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.235 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Steel Comp 303se Overall |
| Material Document And Classification: | Ams 5640 Assn Std Single Material Response Overall Or Astm A582 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL75-5A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.