

**Description**


self-aligning collar assembly, stainless steel, tension application, cadmium plated, HL75 series collar

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL755AW
Minimum Qty (MOQ):	5
NSN:	5320-01-048-5411
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N HL75-5AW Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.355 Inches Minimum And 0.365 Inches Maximum
<b>Collar Overall Height:</b>	0.427 Inches Minimum And 0.457 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.235 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-riquet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HL75-5AW](https://military-fasteners.com/collars/pin_rivet+collars/HL75-5AW) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.