



★ FASTENERS

Military-Fasteners.com

P/N HL75-5AW

Description

self-aligning collar assembly, stainless steel, tension application, cadmium plated, HL75 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL755AW
Minimum Qty (MOQ):	5
NSN:	5320-01-048-5411
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL75-5AW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.355 Inches Minimum And 0.365 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.457 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.235 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL75-5AW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.