

Description

Self-aligning collar, 303 stainless steel - tension application - cadmium plated, HL75 Series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL758A
Minimum Qty (MOQ):	10
NSN:	5320-00-135-3070
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N HL75-8A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Collar Overall Height:	0.522 Inches Minimum And 0.552 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.333 Inches Nominal
End Item Identification:	W/s: Aircraft, Galaxy C-5; Aircraft, Stratofortress B-52; Aircraft, Stratolifter C-135; Aircraft, Hx Unique
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL75-8A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.